

Coral brush Activ is a clean-off carpet for use when soiling is predominantly caused by walked-in dirt, grit, and moisture

Entrance system: A clean-off carpet constructed from high quality 100% polyamide yarn and is designed for use when soiling is predominantly caused by walked-in dirt, grit, and moisture. Coral Brush Activ with Everfort backing is available in rolls of 100, 150, and 200cm widths and pre-cut mats. It is also available in 2 designs and 25 colors.

Width of rolls	6'6"			
Roll Length	90' approx.			
Weight/Square Yard	7.0 lbs/roll			
Quality				
Manufacturing Method/type	tufted, 5/32" cut-pile			
Designs	multi-colored designed/colored			
Pile Material	100% polyamide			
Tuft Base	non-woven polyester			
Backing	EVERFORT vinyl			
Pile installation weight	approx. (32.47 oz. per yard)			
Pile density ISO 8543	approx. 0.00374in per cubic 0.1550 in)			
Pile thickness ISO 1766	approx. (1.27 in)			
Total weight ISO 8543	approx. (8.16lbs per yd ²)			
Total thickness ISO 1765	approx. (0.39in)			
Number of tufts ISO 1763	approx. 81,300 per yd ²)			
Wear classification EN1307	very intensive, class 4			
Comfort classification EN 1307	good, class 3			
Suitability for stairs	N/A			
Suitability for wheelchairs	suitable, class 4			
Antistatic properties	N/A			
Personal Charging EN 1815	<2kV (antistatic)			
Transmission resistance ISO 10965	(10 ¹⁰ ohms)			
Contact sound insulation ISO 140-8	LW = approx. 37 dB			
Sound Absorption ISO 453	Freq.HZ 250 500 1000 2000 4000 0.02 0.07 0.13 0.33 0.45 0.57			
heat transmission resistance ISO 8302	0.18 square meter K/W			
Color Fastness Ratings:				
Light ISO 105/B02	7 on a scale of 1 to 8			
Rubbing ISO 105/X12	5 on a scale of 1 to 5			
Water ISO 105/E01	5 on a scale of 1 to 5			
Seawater ISO 105/E02	5 on a scale of 1 to 5			
Shampoo BS 1006	4 on a scale of 1 to 5			
Organic solvents ISO 150/X05	4-5 on a scale of 1 to 5			
Fire Safety:				
Euroclass EN ISO 13501:2000	C _{fl} s1			
ASTM E648-91a	Class 1 (5.8 KW/m ²)			
BS 476-6	N/A			
BS 4790:1972	Low Radius			
ISO 6925	pass (FF-1-70)			
Architectural floor systems, inc.				
206 Campus Drive, Arlington Heights, IL 60004				
800-323-6792				
www.4afs.com				
info@4afs.com				